

Package: dblog (via r-universe)

October 11, 2026

Title Logging for DBI
Version 0.0.0.9051
Date 2026-10-11
Description Provides logging of DBI methods for arbitrary backends.
License GPL-3
URL <https://dblog.r-dbi.org>, <https://github.com/r-dbi/dblog>
BugReports <https://github.com/r-dbi/dblog/issues>
Imports collections (>= 0.1.4), DBI, glue, methods, purrr, rlang
Encoding UTF-8
Roxygen list(markdown = TRUE)
Collate 'Driver.R' 'Connection.R' 'Result.R' 'deparse.R' 'import.R'
 'make-log-call.R'
Suggests testthat (>= 3.0.0)
Config/testthat/edition 3
Config/roxygen2/version 8.1.1.9000
Repository <https://r-dbi.r-universe.dev>
Date/Publication 2026-10-11 00:29:22 UTC
RemoteUrl <https://github.com/r-dbi/dblog>
RemoteRef HEAD
RemoteSha 9d2c942d7139edf1342d062d6d33ebc01a4ae269

Contents

DBI	2
dblog	2
get_default_logger	3
Index	4

DBI

DBI methods

Description

Implementations of pure virtual functions defined in the DBI package.

dblog

dblog driver and connector

Description

TBD.

Usage

```
dblog(drv, logger = get_default_logger())
```

```
dblog_cnr(cnr, logger = get_default_logger())
```

Arguments

drv	Driver to be wrapped, object of class DBI::DBIDriver .
logger	Logger object, defaults to get_default_logger() .
cnr	Connector to be wrapped, object of class DBI::DBIConnector .

Examples

```
## Not run:  
#' library(DBI)  
Rdblog::dblog()  
  
## End(Not run)
```

get_default_logger	<i>Logging parameters</i>
--------------------	---------------------------

Description

TBD.

Usage

```
get_default_logger()
```

```
make_text_logger(path = NULL)
```

```
make_collect_logger(display = FALSE)
```

Arguments

path	Passed on to <code>cat()</code> for the output. Default: console output.
display	[logical(1)] Set to TRUE to display log entries in addition to writing to a file.

Index

`cat()`, [3](#)

`DBI`, [2](#)

`DBI::DBIConnector`, [2](#)

`DBI::DBIDriver`, [2](#)

`dblog`, [2](#)

`dblog_cnr (dblog)`, [2](#)

`get_default_logger`, [3](#)

`get_default_logger()`, [2](#)

`make_collect_logger`

 (`get_default_logger`), [3](#)

`make_text_logger (get_default_logger)`, [3](#)